

Address & Registered Office: Date of Test: 09.07.2015
Airquee Limited, Unit 2b, Barton Hill Trading Estate, Bristol, BS5 9RD, UK

Product: Sweeper Game 8M

Certificate Of Conformity to EN14960

This certificate relates only to the individual product detailed below. It confirms that at the time of manufacture this product conforms to EN14960.

Product dimensions (m)

D

To remain compliant this product must be tested annually.

To book your test please call 01179 414 918 or visit www.airquee.co.uk for more information

This is the test certificate for your new inflatable. Please keep this in a safe place. This is valid for one year from the date below.

Serial No: P20693 Code: AQ5304 7.9 2.5 7.9 Valid From: 09.07.2015 **User Heights** Certificate Number: P20693 1.5 1.25 1.8 Tag No: **User numbers** Weight Unit 158 kg, Total 238 kg 8 8 8 Pass Fail N/A Structure Security of Seams Material = gloss 630g + 450g + Mehler pvo Stitching Anchor Points Anchor points= 14 pcs/ triangles Anchor Accessories Х Walls & Towers Inside heigh wall = 1.85 m Blower Tube(s) Blower tube length= 1.5 m Position= 1 on rear Zips= 2 pcs(velcro flap+non return flap) Fabric Flame Retardant Fabric Strength Step / Ramp Size Platform height = 0.6 m Grounding Sharp Angles 11 12 Stability Х Ropes Artwork 14 15 Artwork= manual paint no laq UV Air Loss Points Water Gauge Pressure (WGP) Fall Off Height (FOH) WGP= 4.7 inch Fall of hight= 0.6 m Trough depth 20 Thread Netting Netting = black scrim fixed 22 23 Entrapment Deflation / Evacuation Time Markings Identification Notes : **Totally Enclosed Structures** Exits Exit Markings 28 29 Lighting Supports Emergency Lighting Deflation Speed User Area Pressure Slides Wall Heights Notes Run Out Clamber step Slide Sheet Blower Notes: Blower = power= 1*1.5HP + 1*hand fan Size & Type Inlet & Outlet Mesh Accessories= Complet mecanism + 1* 2m Sealed tube + 2* air valve Cable & Plug Casing & Impeller Pat Test Return Flap Signed By: Viorel Constantin Tel: UK - 0845 0094 300 International +44 1179 414 918 Fax: UK - 0845 0095 300 International +44 1179 414 919